



MATERIAL SAFETY DATA SHEET

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER: PM10

PRODUCT NAME: WOOD & PANEL Magic (AEROSOL)

MANUFACTURER'S NAME: Magic American Products, Inc.
26901 CANNON ROAD, SUITE 190
BEDFORD HEIGHTS, OHIO 44146

Information Telephone No.: 800-328-9248
DATE OF PREPARATION: 3/9/06

EMERGENCY TELEPHONE NO.: CHEMTEL 1-800-255-3924

HMIS CODES

Health 2
Flammability 4
Reactivity 0

Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

% by WT	CAS No.	INGREDIENT UNITS	VAPOR PRESSURE
3	74-98-6	Propane ACGIH TLV 2500 ppm OSHA PEL 1000 ppm	760 mm
7	106-97-8	Butane ACGIH TLV 800 ppm OSHA PEL 800 ppm	760 mm
12	64742-47-8	Heavy Aliphatic Solvent ACGIH TLV Not Available OSHA PEL Not Available	0.1 mm
7	8042-47-5	Paraffinic Mineral Oil ACGIH TLV 5 mg/m3 as Mist OSHA PEL 5 mg/m3 as Mist	

Section 3 -- HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE: INHALATION of vapor or spray mist.

EYE or SKIN contact with the product, vapor or spray mist.

EFFECTS OF OVEREXPOSURE: EYES: Irritation.

SKIN: Prolonged or repeated exposure may cause irritation.

INHALATION: Irritation of the upper respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE: Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists. Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None generally recognized.

CANCER INFORMATION: For complete discussion of toxicology data refer to Section 11.

Section 4 -- FIRST AID MEASURES

EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.

INHALATION: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

INGESTION: Do not induce vomiting. Get medical attention immediately.

Section 5 -- FIRE FIGHTING MEASURES

FLASH POINT: Propellant < 0 F **LEL:** 1.3 **UEL:** 9.5

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Alcohol Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may explode (due to the build-up of pressure) when

exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES: Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible auto-ignition or explosion when exposed to extreme heat.

=====
Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Ventilate the area. Remove with inert absorbent.

=====
Section 7 -- HANDLING AND STORAGE

STORAGE CATEGORY: Not Available

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively. During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition. Consult NFPA Code. Use approved Bonding and Grounding procedures. Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

=====
Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

PRECAUTIONS TO BE TAKEN IN USE: Use only with adequate ventilation. Avoid contact with skin and eyes. Avoid breathing vapor and spray mist. Wash hands after using.

VENTILATION: Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION: If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Sec. 2.

PROTECTIVE GLOVES: None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

EYE PROTECTION: Wear safety spectacles with un-perforated side-shields.

OTHER PRECAUTIONS: Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

=====
Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

PRODUCT WEIGHT: 7.38 lb/gal 884 g/l

SPECIFIC GRAVITY: 0.89

BOILING POINT: <0 - 484 F <-18 - 251 C

MELTING POINT: Not Available

VOLATILE VOLUME: 91%

EVAPORATION RATE: Faster than ether

VAPOR DENSITY: Heavier than air

SOLUBILITY IN WATER: N.A.

PH: 7.0

VOLATILE ORGANIC COMPOUNDS (VOC Theoretical):

Volatile Weight 22.36% Less Water and Federally Exempt Solvents

=====
Section 10 -- STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID: None known.

INCOMPATIBILITY: None known

HAZARDOUS POLYMERIZATION: Will not occur

HAZARDOUS DECOMPOSITION PRODUCTS: By fire: Carbon Dioxide, Carbon Monoxide

=====
Section 11 -- TOXICOLOGICAL INFORMATION

CHRONIC HEALTH HAZARDS: No ingredient in this product is an IARC, NTP or OSHA listed carcinogen. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

TOXICOLOGY DATA

CAS No. Ingredient Name

74-98-6 Propane

LC50 RAT 4HR Not Available

LD50 RAT Not Available

106-97-8 Butane

	LC50	RAT	4HR	Not Available
	LD50	RAT		Not Available
64742-47-8	Heavy Aliphatic Solvent			
	LC50	RAT	4HR	Not Available
	LD50	RAT		Not Available
8042-47-5	Paraffinic Mineral Oil			
	LC50	RAT	4HR	Not Available
	LD50	RAT		Not Available

=====
Section 12 -- ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: No data available.

=====
Section 13 -- DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

=====
Section 14 -- TRANSPORT INFORMATION

No data available.

=====
Section 15 -- REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
---------	-------------------	---------	-----------

No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

=====
Section 16 -- OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.